A02-10-100: Semi Automatic Vertical Autoclave

Suitable for the sterilization of:

- · Liquids such as nutrient media and buffer solutions
- Solid items such as pipettes, tubes and filters
- Glassware and plastic articles
- Waste sterilization



Features:

- Heat-resistant plastic covering on lid Prevents contact with hot parts and protects from burning.
- Pressure-dependent door lock Prevents the door from being opened when under pressure.
- Door lock safety switch Prevents the sterilization program from being started if the door has not been closed properly.
- Excess temperature safety device Switches off the heating elements if too high a temperature is attained.
- Overpressure valve Releases over pressure in order to prevent high pressure risk.

Technical Specification:

Chamber Volume (liter): 85

Chamber Size (øxDepth in mm): 380x690 Voltage(nominal +/-10%) 50/60Hz (V): 380-400 **Heating Capacity (Kw):** 6.0

Ambient Temperature (°C): 5 to 40 degrees Control: Semi Automatic **Dimensions* WidthxHeightxDepth (mm):** 650x950x500

Shipping Weight: 116 ka

Loading Capacity:

Erlenmeyer	Nr. of bottles	Schott-Duran	Nr. of Bottles
250 mL	4 x 12	250 mL	4 x 18
500 mL	3 x 7	500 mL	3 x 11
1000 mL	2 x 4	1000 mL	2 x 8
2000 mL	2 x 3	2000 mL	2 x 4
3000 mL	2 x 2	5000 mL	2
5000 mL	1	10000 mL	1

^{*}Dimensions refer to unit housing including levelling feet. Technical data are subject to change without prior notice.