

Unparalleled Clarity and Confidence



Any patient. Anywhere. Anytime.

This isn't just our most advanced point-of-care ultrasound solution ever, it's YOURS.

See More. Do More. **Sonosite PX**

Unparalleled Clarity and Confidence

Inspired, informed and improved by thousands of hours working side-by-side with clinicians on the front lines of medicine, Sonosite PX point-of-care ultrasound system delivers the most advanced image clarity Fujifilm Sonosite has ever offered, to give clinicians an unparalleled level of confidence for diagnostic and procedural applications.

This isn't just our most advanced point-of-care ultrasound solution ever, it's YOURS.







Designed for the **Human Touch**

The human touch is crucial when it comes to point-of-care ultrasound. That's why Sonosite PX has been designed around every detail for the way clinicians work and deliver care.

Touch and Physical Controls

Intuitive touch panel and physical buttons for quick access to the most-used controls. Unique raised buttons allow clinicians to make adjustments via feel. Sonosite PX can be operated with gloves and a sterile drape.

Workflow Efficiency Features

The streamlined user interface improves workflow, allowing clinicians to find controls quickly with fewer touches. Exam types are optimised with most-needed annotations and calculations.









Get Closer at the Point of Care

We listened and listened some more, working with clinicians across the globe. Sonosite PX was created and inspired by the way they need to deliver care, wherever they deliver it.

Adaptable Positioning

Adaptable horizontal to vertical work surface allows clinicians to adjust Sonosite PX for optimal bedside ergonomics and bring it closer to the bedside.*

Closer Access

The low-profile wheelbase fits under most beds for closer access, especially important while operating the system across the bed. Front and side levers simplify height adjustments.

Adjustable Height System height can be raised or lowered for a

wide range of users.

Adaptable Positioning

Work surface adapts from horizontal to vertical with a push or pull of the handle.





A Whole New Vision of Vision

Sonosite PX point-of-care ultrasound solution delivers the most advanced image clarity Sonosite has ever offered, aided by a new family of transducers, proprietary speckle reduction technology and improved colour performance.

Nerve Blocks

6

*

esia Centre Territori territori

> Better visualise sonographic landmarks when precision and accuracy is paramount during complex blocks.

Cardiac Assessments

Effectively assess cardiac function with optimal frame rates, improved sensitivity and an enhanced colour map.

Musculoskeletal Exams

See anatomy details accurately in small joints such as fingers to better identify the tell-tale signs of inflammation.



Environment Inspired

Optimised for the way you move. The way you think.

The agile, small footprint Sonosite PX stand offers maneuverability and dedicated features to keep your system organised and stocked with the essentials.

Data Management and Connectivity

Wifi, Ethernet port, 1080p digital video output compatible with 1080p displays, (4) USB 2.0 ports, (2) USB 3.0 ports, (1) dedicated USB port for optional printer.[†]

Durable Transducer Holders

Integrated holders (no more cups) for simplified clean up and ease of use.

Triple Transducer Connect

Three transducer ports so your most-used transducers are at the ready with the touch of a button.

Versatile Storage Solutions

The flexible storage system adapts to left or right side needs—gel holder, wipes holder, storage bin and lockable drawer to secure supplies.

Cord Management

Power cords are confined within the column to help prevent tangles.

Cable Management System

Cable catcher and hooks help prevent tangled transducer cables. Even at the lowest stand height, cables are less likely to drag on the floor.

Low-Profile Wheeled Base

The low-profile wheel base helps position the system close to the bedside.



Peripheral Accessories

Barcode Scanner

Save time by automatically linking patient data to the ultrasound scan. English only, where available.

Barcode Expressions

Auto-populate physician ID and patient information with customised software for your Sonosite Barcode Scanner. English only, where available.

Medical Grade Printer

Add the optional Black and White Printer to print ultrasound studies.

Needle Guide Starter Kits

Improve positioning to help guide needles to an exact target on the first attempt.

PowerPark Cordless Charging Station

Dock the system in a central location while the battery charges for cord-free use. Cord-free use eliminates power cords dragging on the floor, risking contamination. No power cords to clean and disinfect.



Flexible Cardiac Functionality

Sonosite PX delivers flexible cardiac functionality for novice to advanced users to support the important challenge of assessing cardiac function.



Guide Needles Precisely

Auto Steep Needle Profiling helps in-plane needle visualisation from multiple angles with one system interaction. The clinician simply advances the needle at the angle optimal to reach the target.



Education at Your Fingertips

Sonosite is dedicated to clinician education. More than 150 scan-along education tutorials are onboard for COVID-19, diagnosis, procedures, pathology, and system and transducer use.



Rest Assured with Data Security

Sonosite PX includes robust security features to keep patient information safe and networks secure. The system meets FIPS199, FIPS200, and NIST 800-53.

WI HIN

JUSONOS

Scan with Confidence

Sonosite designs, manufactures and tests transducers in-house. Our transducers aren't only durable, they're also made for superior imaging in the most demanding environments.

- IPX7 rated for immersion**
- Drop-tested to 1 metre
- · Sonosite-manufactured transducers are covered by a Sonosite 5-year standard warranty



C5-1 • 5-1 MHz Curved Scan Depth: 30 cm

Exam Types: Abdomen, Lung, Nerve, Musculoskeletal, Early Obstetrics,



IC10-3 10-3 MHz Curved Scan Depth: 15 cm

Exam Types:




L19-5 19–5 MHz Linear Scan Depth: 6 cm

Exam Types: Arterial, Lung, Musculoskeletal, Nerve, Ophthalmic, PIV, Superficial,

Optional Needle Guide Starter Kit

Variable angle, in-plane guide Multiple-depth transverse, out-of-plane guide Disposable in-plane guide



P-1



L12-3 12-3 MHz Linear Scan Depth: 9 cm

Exam Types: Carotid, Lung, Musculoskeletal, Nerve, Ophthalmic, Superficial, Venous



L15-4 15-4 MHz Linear Scan Depth: 6 cm

Exam Types: Musculoskeletal, Nerve, Superficial,



P5-1 5-1 MHz Phased Scan Depth: 35 cm

Exam Types: Cardiac, Focused Cardiac, Lung, Obstetrics, Orbital, Transcranial Doppler (TCD)

Sonosite PX Ultrasound System and Stand Specifications

anoral System and Stand Specifications

| General System and S | tand Specifications |
|--|---|
| Dimensions width x height | unless otherwise stated |
| Stand Dimensions (footprint width x depth) | 28.3 inches x 28.3 inches 720 mm x 720 mm |
| Height Maximum (system and stand) | 65 inches/1650 mm monitor raised |
| Height Minimum (system and stand) | 42.2 inches/1072 mm monitor lowered |
| Height Adjustment Range | 9.8 inches/249 mm |
| Work Surface Adjusts Monitor Angle Work Surface Angle | 0 to 140 degrees 15 degrees from horizontal 55 degrees from horizontal |
| Weight (system and stand) (system only) | 85.1 lbs/38.6 kg 16 lbs 10 oz/7.5 kg |
| System Controls | Touch panel and physical buttons |
| Touch Panel Controls Size | 10 inches x 5.7 inches 256 mm x 145 mm |
| Clinical Monitor Monitor Size Display Size Image Size | 15.6 inches/396 mm 13.5 inches x 7.6 inches 344 mm x 194 mm 8.1 inches x 6.1 inches 207 mm x 155 mm |
| Screen Resolution (minimum) Display Size Image Size | 1920 x 1080 pixels 1152 x 864 pixels |
| Transducer Connections (system and stand) (system only) | (3) Transducer ports (1) Transducer port |
| Liquid Ingress Protection Rating (system only) | IP22 |
| Immersion Rating (transducers) | IPX7 |
| Operating System | Windows 10 IoT Enterprise 2019 LTSC |
| Architecture | Digital broadband |
| Dynamic Range | Up to 183 dB |
| Gray Scale | 256 shades |
| HIPAA Compliance | FIPS199, FIPS200, and NIST 800-53 |

User Interface

Physical Buttons: Time Gain Compensation (TGC), gain wheel, auto gain, depth, select, update, touchpad, annotations, calculations, caliper, image save, clip save, freeze, colour, M-Mode, Doppler, 2D Touch Panel: Projected Capacitive (PCAP) touchscreen Display Formats for Duplex Imaging: 1/3 and 2/3, 1/2 and 1/2, 2/3, and 1/3, side by side, and full screen duplex

Doppler Controls: Doppler Mode (PW, CW, and TDI), angle, steer, scale, baseline, invert, sweep speed, power, wall filter, sample volume, auto trace, gain, and volume

Image Modes

2D Broadband Imaging, Tissue Harmonic Imaging, Pulse Inversion Harmonic Imaging, B-Mode, M-Mode, Colour Velocity Doppler (CVD), Colour Power Doppler (CPD), Colour Variance Mode (cardiac only), Pulsed Wave Doppler (PW), Pulsed Wave Doppler Simultaneous, Tissue Doppler Imaging (TDI), Continuous Wave Doppler (CW)

Image Processing

Sonosite proprietary speckle reduction algorithm, SonoADAPT Imaging Technology, SonoMB^{*} Multi-beam Technology, dual imaging, Time Gain Compensation (TGC), AutoGain, restore default gains, dynamic range, duplex imaging, Triplex, 8x live zoom, Write zoom

Cine Processing: Dynamic range

Cine Processing: Zoom

2D Image Optimisation: Resolution/General/ Penetration (Res/Gen/Pen), Colour Doppler flow optimisation, colour variance mode, colour compare, 2D sector control (steerable), output power control

Needle Profiling

(Auto Steep Needle Profiling available on these transducers and exams)

C5-1: Musculoskeletal, Nerve, Spine L19-5: Arterial, Musculoskeletal, Nerve, PIV, Superficial,

Venous L12-3: Arterial, Breast, Musculoskeletal, Nerve,

Superficial, Venous

L15-4: Arterial, Breast, Musculoskeletal, Nerve, Superficial, Venous

Needle Guide Starter Kits: C5-1, IC10-3, L19-5, L12-3, L15-4

Measurements

2D: Distance (10 measurements), area, circumference, ellipse, manual trace, volume, target depth, angle Doppler: Velocity, velocity pair, slope, time, manual trace, auto trace, heart rate, resistive index, pulsatility index, systolic/diastolic ratio, volume flow, velocity time integral, TAM, TAP

Automatic Trace Results (determined by exam type): Velocity time integral, peak systolic velocity, end diastolic velocity, mean diastolic velocity, resistive index, pulsatility index, TAP, gate depth, systolic/ diastolic ratio, velocity max, velocity mean, pressure gradient max, pressure gradient mean Editable results data sheets and reports

FUJIFILM SONOSITE Value from Innovation

FUJIFILM Sonosite, Inc.

Worldwide Headquarters 21919 30th Drive SE, Bothell, WA 98021-3904 Tel: +1 (425) 951 1200 or +1 (877) 657 8050 Fax: +1 (425) 951 6800 **sonosite.com**

FUJIFILM Sonosite BV

European Headquarters Joop Geesinkweg 140, 1114 AB Amsterdam, Netherlands Tel: +31 20 462 0000

Sonosite Worldwide Offices

Data Management and Connectivity

System and Stand: Wifi, Ethernet port, 1080p digital video output compatible with 1080p displays, (4) USB 2.0 ports, (2) USB 3.0 ports, (1) dedicated USB port for printer, DC input for AC or stand battery power System Only: (2) USB 3.0 ports

ECG connector Storage capacity alert Auto delete function IPv4 and IPv6 networking Supports automatic time reconciliation with a time server

Wireless Solutions

2.4 GHz and/or 5 GHz Wireless: 802.11 (A, B, G, N, and AC networking)

Key Management Protocols: WEP64, WEP128, WPA/ WPA2 (personal and enterprise)

DICOM Workflow Management

Store for images, clips, and structured reports, media storage (USB export), storage commitment, modality worklist, Modality Performed Procedure Step (MPPS)

Data Security

System meets Federal Information Processing Standards (FIPS) for moderate security control selections per FIPS199, FIPS200, and NIST 800-53 Secure boot User and role based authentication

LDAP support Security Policies: Open, WEP, Radius, WPA, WPA2

Complex password rules support Federal System Use Notification support Emergency mode support Secure DICOM communication support

Data Encryption for Data at Rest: FIPS 140-2 validated encryption algorithms

Data Encryption for Data in Transit: FIPS 140-2 validated encryption algorithms System wide white-listing Hardened operating system and services System firewall

MDS2 located on Sonosite.com

Stand Includes

Adjustable stand head, input/output connections, (4) transducer holders, Triple Transducer Connect, cable management system, dual gel holder, wipes holder, storage bin, lockable drawer, stand battery, cord wrap, power cord

Casters: (4) independent locking wheels

Warrantv

Sonosite offers an industry-leading, 5-year standard warranty on most ultrasound systems and Sonositemanufactured transducers to ensure your equipment is protected. Learn more on sonosite.com

Supported Languages

System User Interface Languages: English, French, German, Italian, Japanese, Spanish, Simplified Chinese

- When Sonosite PX is used on the stand. ** Protected against water immersion for 30 minutes at a depth of up to 1 metre
- † Off the stand, Sonosite PX has (2) USB 3.0 ports.

Any patient. Anywhere. Anytime.

| FUJIFILM Sonosite Ltd–United Kingdom +44 1462 341 151 |
|---|
| FUJIFILM Sonosite SARL-France +33 182 880 702 |
| FUJIFILM Asia Pacific Pte. Ltd +65 6383 9933 |
| FUJIFILM (China) Investment Co., Ltd +86 21 5010 6000 |
| FUJIFILM Medical Co., Ltd.–Japan +81 3 0418 7190 |
| FUJIFILM Middle East (FZE)+971 4 887 8722 |

SONOSITE and the SONOSITE logo are registered and unregistered trademarks of FUJIFILM Sonosite, Inc. in various jurisdictions. FUJIFILM is a registered trademark of FUJIFILM Corporation in various jurisdictions. All other trademarks are the property of their respective owner Copyright © 2021 FUJIFILM Sonosite, Inc. All rights reserved. Subject to change.