

Meet the changing needs of your patients.

Trilogy 100, advanced ventilator technology

Simple ventilation. Sophisticated technology.

Respironics, the originator of bi-level technology, has developed Trilogy 100, a remarkably versatile ventilator that meets the needs of adult and pediatric patients alike. Leveraging well-known Respironics technology, Trilogy 100 provides clinicians with an array of treatment options by delivering Volume Control Ventilation or Pressure Control Ventilation through either noninvasive or invasive methods with advanced leakage compensation. This built-in flexibility makes Trilogy 100 ideal in treating a wide range of respiratory conditions or those respiratory conditions that require frequent changes to the patient's prescription.



Trilogy 100's versatility allows you to deliver portable or in-home patient therapy using an AC power source, an external battery, a detachable battery or the device's internal battery. The detachable battery provides up to three hours of portable therapy while the internal battery delivers three additional hours of cordless operation.

Another of Trilogy 100's powerful features is DirectView – a highly sophisticated reporting software system. DirectView allows logging and recording of events and treatment actions and is easy to use for both physicians and caretakers.

Features:

- For adults and children (> 5 kg)
- Volume and pressure modes
- Invasive and non-invasive capabilities
- Lightweight design (11 lbs, 5 kgs)
- Internal and detachable batteries
- Easy-to-use interface
- DirectView reporting software-ready
- Dual prescription settings
- AVAPS (Average Volume Assured Pressure Support) technology
- Digital Auto-Trak
- Removable air path



Ordering information

| ltem no. |
|-----------|
| 1054096 |
| 1054097 |
| 1054655 |
| AU1054096 |
| LA1054096 |
| CA1054096 |
| 1054260 |
| |

Specifications

| Environmental | |
|--|---|
| | F°C 40°C |
| Temperature | 5°C – 40°C |
| Relative humidity | 15% – 95% |
| Atmospheric pressure | 110 kPa to 60 kPa |
| Physical | |
| Weight | 11 lbs, 5 kgs |
| Size | 6.6 x 11.2 x 9.3", |
| | 16.68 x 28.45 x 23.52 cm |
| Controls | |
| Circuit types | Active with PAP, passive |
| Ventilation types | Volume control, pressure |
| | Control, bilevel |
| Volume modes | AC, SIMV (w/PS), CV |
| Pressure modes | CPAP, S, S/T, T, PC-SIMV (w/PS) |
| IPAP | 4 – 50 cm H,O |
| EPAP | |
| EFAF | 0 - 25 cm H ₂ O for active circuits |
| CDAD | 4 - 25 cm H ₂ O for passive circuits |
| CPAP | 4 - 20 cm H ₂ O for passive circuits |
| PEEP | 0 - 25 cm H ₂ O for active circuits |
| | 4 - 25 cm H ₂ O for passive circuits |
| Pressure support differential | 0 – 30 cm H ₂ O |
| Tidal volume | 50 – 2000 ml |
| Breath rate | 0 – 60 for AC mode |
| | 1 – 60 for all other modes |
| Inspiratory time | 0.3 – 5.0 secs |
| Rise time | 1 – 6 |
| Ramp start pressure | 0 – 25 cm H ₂ O for active circuits |
| · ····· F · ···· · F · · · · · · · · | 4 - 25 cm H ₂ O for passive circuits |
| | 4 - 19 cm H ₂ O in CPAP mode |
| Ramp length | Off, $5 - 45$ minutes |
| Flex | Off, 1 – 3 |
| | 1 - 9 l/min |
| Flow trigger sensitivity | 10% - 40% |
| Flow cycle | 4 – 60 BPM |
| Apnea rate Measured patient parameter | |
| Tidal volume | 0 – 2000 ml |
| | |
| Minute ventilation | 0 – 99 l/min |
| Leak rate | 0 – 200 l/min |
| Respiratory rate | 0 – 80 BPM |
| Peak inspiratory flow | 0 – 200 l/min |
| Peak inspiratory pressure | 0 – 99 cm H ₂ O |
| Mean airway pressure | 0 – 99 cm H ₂ O |
| % Patient triggered breaths | 0 – 100% |
| I:E ratio | 9.9:1 to 1:9.9 |
| Alarms | |
| Circuit disconnect | Off, 10 – 60 secs |
| Apnea | Off, 10 – 60 secs |
| High tidal volume | Off, 50 – 2000 ml |
| Low tidal volume | Off, 50 – 2000 ml |
| High minute ventilation | Off, 1 – 99 l/min |
| Low minute ventilation | Off, 1 – 99 l/min |
| High respiratory rate | Off, 4 – 80 BPM |
| Low respiratory Rate | Off, 4 – 80 BPM |
| Low respiratory Nate | |

Refer to the Trilogy 100 clinical manual for complete product information.

Respironics, DirectView, Auto-Trak, AVAPS and Trilogy are trademarks of Respironics, Inc. and its affiliates. All rights reserved.



©2009 Koninklijke Philips Electronics N.V. All rights are reserved. Philips Healthcare reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.

 $\ensuremath{\mathsf{CAUTION}}\xspace$ to sale by or on the order of a physician.

Broudy KB 6/12/09 MCI 4102381 PN 1059273

Europe, Middle East, Africa +33 1 47 52 30 00 Asia Pacific +65 6298 1088 Philips Respironics 1010 Murry Ridge Lane Murrysville, PA 15668

Customer Service +1 724 387 4000 800 345 6443

www.philips.com/respironics 800 345 6443