

# MEDICAL DEVICES



## Volumat Agilia Infusion Pump



# VOLUMAT AGILIA

## INFUSION

FLOW RATE RANGE	1-1200 ml/h in normal mode (1ml/h increment). 0.1- 99.9 ml/h in micro mode (0.1 ml/h increment). Flow rate can be limited according to drug name (soft and hard limits) with our Vigilant® IV Medication Safety System.
FLOW RATE ACCURACY	+ / -5% and even better in most clinical situations.
VOLUME TO INFUSE	1-9999 ml in normal mode, 0.1-999.9 ml in micro mode.
INFUSION SETTINGS MODES	5 setting modes are available: ml/h only (if optional drop sensor is used), Volume / Time with automatic calculation of the flow rate, Volume + Flow rate, Flow rate + Time, combination of Volume + Time + Rate. Possibility of a delayed start-up.
TIMES OF INFUSION	From 0h01' to 168h00 with warning when recommended duration of set use is elapsed.
PRIMING	Manual or by using the purge/prime function of the pump.
OCS PATENT	The Occlusivity Check System is the only auto-test to check the good working order of the pump in association with its set and thus preventing risk of free-flow.
BOLUS	1200 ml/h, adjustable from 50 ml/h to 1200ml/h by 50 ml/h increments.
KVO	Automatic Keep Vein Open rate of 3ml/h (adjustable from 1 to 20 ml/h) when volume limit is reached.
PAUSE	Programmable from 1 minute to 24 hours, increments from minute to minute.
DATA LOG EVENT	1500 data log events in real time.
NIGHT MODE	The night mode decreases the brightness of the screen, and the green lights. The key beep can eventually be turned off. The night mode can be programmed manually or automatically in a variable time range.
PROGRAMMING MODES	No drug names: infusion without any display of the drug names. Drug labelling: infusion with the drug names displayed. Vigilant® Drug'Lib: the secured IV administration mode by soft and hard limits.
DRUG LABELLING	Display of the drug name based on a list of 50 pre-set drug names.
DRUG LIBRARIES	Customized drug library with Vigilant®, the IV Medication Safety Solution. Up to 4 different drug libraries. Each drug is defined by: drug name, default rate, min and max rates (soft and hard limits), and infusion mode. Up to 100 drugs.
KEYBOARD PROTECTIONS	Possibility to lock the keyboard to prevent involuntary change of setting.

## PRESSURE MANAGEMENT

PRESSURE MODE	2 modes available: variable (from 50 to 750 mmHg, 50 mmHg increment) or 3 pre-set levels.
DPS	The Dynamic Pressure System - DPS - warns of pressure variations. A risk of obstruction or a possible leak in the infusion line can thus be anticipated.
PRESSURE MONITORING	Graphic representation of the pressure in the infusion line and of the pressure limit thanks to the pictograms.
ANTI-BOLUS SYSTEM	Reduces significantly bolus after occlusion release (0.2 ml max).

## ALARMS / PRE-ALARMS / SECURITY

PUMP STATUS	Green for infusion in progress, orange for pre-alarm and warnings, red for alarm. Visibility up to 5 meters. All alarms are expressed by means of light indicators, written words, pictograms and sound beep.
SET INSTALLATION CONTROL	Door's closing, set positioning, SafeClip control, OCS test.
INFUSION CONTROL	End of infusion, imminent end of infusion, downstream occlusion, upstream occlusion, line disconnection, air in line, under flow rate, over flow rate, empty container, unconfirmed setting, end of pause, unauthorised flow rate (hard or soft).
DEVICE CONTROL	Motor rotation check, power source indication, mains power disconnection, low battery, discharged battery, technical fault, watchdog check, communication connection failure.
MAINTENANCE	Preventive maintenance warning.

## TECHNICAL SPECIFICATIONS

PUMPING MECHANISM	2nd Generation linear peristaltic pumping system with software adjustments and compensations.
DISPLAY	Blue graphic LCD monochrome, size 66 mm x 33 mm (128 x 64 pixels).
SWINGLOCK CLAMP	Versatile clamp that allows the fixation to a rail or to a pole / pole: 20-40 mm maximum; rail: 25-35 x 10 mm.
STACKABILITY	Up to 3 devices self - stackable on a pole with a safe handle.
DIMENSIONS (H/W/D) / WEIGHT	145 x 130 x 135 mm / Weight: ~2000 gr.
BATTERY	Li-Ion, battery life at least 8 hours at 100 ml/h, remaining battery life and battery charge level available on the display.
COMPLIANCE STANDARD	EN/IEC 60601-1 and EN/IEC 60601-2-24 / CE 0459 marking in compliance with the EEC 93/42 European Medical Device Directive / EMC.
WATERPROOFNESS	IP22.
ELECTRICAL COMPLIANCE	Protection against leakage current: CF type - protection against electric shocks: class II.
POWER SUPPLY	100-240 Vac / 50-60 Hz with standard cable, 10 Vdc with specific DC cable.

## VOLUMAT LINE ADMINISTRATION SETS

FREE-FLOW PROTECTION	All sets integrate the SafeClip that automatically clamps the line to avoid any risk of free flow when the door is opened.
PUMPING SEGMENT	The silicone pumping segment allows a tight flow rate accuracy as well as long term performances.
MATERIAL	All Volumat Line infusion sets are DEHP-free & Latex-free. PVC-free and opaque materials are available on some sets.
NEEDLE-FREE ACCESS	Some sets integrate a needle-free Y injection site to protect the medical staff against the risk of needle-stick injuries.

Due to our policy of continuous product development as well as changes in standards, the features described are subject to change. Please contact us for current situation.



### Manufacturer:

Fresenius Vial S. A. S.  
Le Grand Chemin  
38590 Brézins  
France  
Tel.: +33 (0)4 76 67 10 10  
Fax: +33 (0)4 76 67 11 34

A Company of Fresenius Kabi

## Agilia

The Agilia family offers a complete range of infusion pumps, syringe pumps, accessories and disposables to cover all major IV drug administration needs.

### Injectomat® Agilia



HANDY

### Injectomat® MC Agilia



COMPREHENSIVE

### Injectomat® TIVA Agilia



ANAESTHESIA DEDICATED

### Volumat Agilia



SMART

### Volumat MC Agilia



ADVANCED

### Links & Accessories



### Administration Sets



### Maintenance Tools

