

ORDERING INFORMATION

REF

6875 hana® Orthopedic Surgery Table

SPECIFICATIONS

Table Top Length48.5 in. (123 cm)
Table Length w/Spars 124 in. (315 cm)
Table Top Width21.5 in. (55 cm); 10" (25 cm)
near perineal post
Table Top Height Range ..30 in.-50 in. (76 cm-127 cm)

Trendelenburg / Reverse Trendelenburg 12°
Lateral Tilt12°
Leg Spar Articulation28° up, 35° down
20° adduction, 45° abduction
Patient Weight Capacity 450 lbs. (205 kg)

PRODUCT FEATURES

Carbon Fiber Table Top
Auxiliary Control
Manual Floor Locks
Physician Controlled Foot Pedal
Accessory Side Rails
Stainless Steel Base
Light Weight Spars
AC or Battery Operation
Replaceable Control Module
Spherical Spatial Positioning System (SSPS™)

POSITIONING CAPABILITIES

Supine
Lateral

MIZUHOSI

MIZUHO OSI



30031 AHERN AVENUE
UNION CITY, CA 94587-1234 USA
TELEPHONE: 510-429-1500
TOLL FREE: 800-777-4674
FAX: 510-429-8500
INTERNATIONAL: 001-510-429-1500
WWW.MIZUHOSI.COM
WWW.NEWHIPNEWS.COM

ISO certified by TÜV Rheinland® of North America



Note: Mizuho OSI is constantly improving its products. All specifications are subject to change without notice. *Patent No. : US 7,824,353 B2

Tempur-Pedic® is a registered trademark of Tempur-Pedic® Medical, Inc.

Mizuho OSI is a Delaware Corporation. Manufactured in the USA

2013 ©Mizuho OSI REF NW0465 REV D

STANDARD COMPONENTS

Hand Pendant
Swivel Mount for Hand Pendant
Femoral Hook Classic Right¹
Femoral Hook Classic Left¹
Femoral Hook Support Assembly (2)
Femur Lift Extension¹ (2)
Femur Lift, Left¹
Femur Lift, Right¹
Femur Lift Foot Pedal
Traction Hook Extension
Total Knee Flexion and Support System™
Well Leg Support Adaptor
Well Leg Support Assembly
Articulating Bracket
Radiolucnet Leg Spars (2)
Traction Boot, Small Pair
Traction Boot, Large Pair
Arm Boards with Pad (2)
Lateral Perineal Post and Pad Assembly
Perineal Post and Pad, Adult
Patient Safety Strap (90 in.)
hana® Table Cover
Tempur-Pedic® Medical Table Top Pad, 2 in. (5 cm)

ETL Approved
120 VAC 60 Hz
230 VAC 50 Hz
100 VAC 50/60 Hz

OPTIONAL ACCESSORIES

REF

6875-500 hana® Cart
6850-170 Lower Leg Support
5855-61 Accessory Clamp
6850-487 Traction Boot, X-Large, Pair
6875-2761 hana® Fracture Kit
5857 Cross Arm Support
5393 Clark Socket
5855-411 Tibia Traction Upright
6850-25 Tibia Traction Boot Adaptor
5855-345 Traction Unit
5855-440 Traction Foot Plate
3369 Hip Arthroscopy Perineal Post, 6 in.

ECREP

EMERGO EUROPE
MOLENSTRAAT 15
2513 BH THE HAGUE
THE NETHERLANDS
TEL: (31) (0) 70 345-5870
FAX: (31) (0) 70 346-7299

hana®

hana® ORTHOPEDIC SURGERY TABLE

FOR EXISTING AND EVOLVING ORTHOPEDIC PROCEDURES



MIZUHOSI

BRINGING INNOVATION TO THE TABLE.®

A SUPERIOR TABLE FOR ORTHOPEDIC PROCEDURES

ANTERIOR APPROACH TO TOTAL HIP ARTHROPLASTY (THA)

IM NAILING FEMUR

IM NAILING TIBIA

hana[®]

HIP PINNING

HIP ARTHROSCOPY

TOTAL HIP RESURFACING

TOTAL KNEE ARTHROPLASTY

SUPINE AND LATERAL POSITIONING



OPTIMIZES ANTERIOR APPROACH TO THA

The hana[®] enables the surgeon to replace the hip through a single incision, anterior approach without detachment of muscle from the pelvis or femur. The table allows hyperextension, abduction, adduction and external rotation of the hip for femoral component placement - a positioning option not possible with conventional tables. The lack of disturbance to the lateral and posterior soft tissues provides immediate stability of the hip after surgery.



FACILITATES MIS KNEE PROCEDURES

- Total Knee Flexion and Support System™ accommodates knee procedures including total knee replacement



EXCEPTIONAL TABLE MANEUVERABILITY

- Aids surgeon in articulation of lower extremities
- Spars include Spherical Spatial Positioning System (SSPS™)
- New fracture kit helps support all lower extremities fracture procedures



EXTENSIVE IMAGING CAPABILITY

- Carbon fiber construction
- Radiolucent cantilever top
- Radiolucent leg spars for uninterrupted imaging
- Unrestricted C-arm access



TEMPUR-PEDIC® MEDICAL PAD TECHNOLOGY

- Equalizes pressure load on patient during surgery
- Contours to patient anatomy with support
- Enhances patient comfort and safety

SOLID STABILITY

- Excellent rigidity
- 450 lb. (205kg) patient capacity
- Low table profile for easy patient transfer

ENHANCED SERVICEABILITY

- Continuous LED Monitoring System
- Replaceable Control Module



CONTROLLED FEMORAL LIFT

- Supports Anterior Approach to THA
- Utilizes a patented Femoral Hook System
- Surgeon controls powered femoral lift
- Provides improved surgical access for femoral canal preparation and femoral component placement



FEMUR LIFT FOOT PEDAL

- Power control for raising and lowering Femoral Lift Support Assembly



AUXILIARY CONTROLS



TRACTION BOOTS

- Allow precise control of patient position, manipulation and traction



POWERED HAND PENDANT



REPLACEABLE CONTROL MODULE

- Simple and easy serviceability
- AC or Battery operation

