

Leica DM100 & Leica DM300

Affordable Innovation for the First-time Scientist



Affordable Innovation for the Next Generation of Scientists

Students learn best when their equipment is easy to use and constructed to be robust enough for trouble free operation each day.

Leica Microsystems, with 165 years of microscope design and manufacturing experience, combines the latest technology in optics, mechanics, and illumination in the new Leica DM100 and DM300 student microscopes. These microscopes provide students with the capabilities they need to study the finest details in all the life sciences.

Construction that lasts

> Focus drive design has been proven in the clinical laboratory

Brilliant illumination

Leica EZLite™ LED illumination produces crisp, clear images

View the finest details


Outstanding optical quality reveals the finest specimen details



Convallaris – Lily of the Valley




Taste Buds




Sunflower




Giant Chromosomes




Mouse Embryo



Squamos Epithelium



Mouse Embryo



Parotid Gland









Benefits: Leica DM100 & DM300

Robust construction:

- Maintenance-free, sealed, brass shaft, focus mechanism; the same design that is used in Leica Microsystems' clinical microscopes provides accurate focus control over the life of the microscope
- Spring-loaded, high-magnification objectives prevent broken specimen slides
- Designed to International Safety Standards

Optimized Illumination and Optics:

- LED illumination saves the cost of replacement lamps and provides a cool white light for over 20 years of average use at 80% lower energy consumption
- › Leica EZLite™ illumination system provides an evenly illuminated field of view for accurate specimen viewing
- The illumination system provides stable, true daylight quality with a wide brightness ratio of 200 to 1

 Superb optical performance as a result of the illumination, objective, viewing tube, and eyepiece working seamlessly together

Student Friendly:

- Coaxial focus mechanism for intuitive control
- Compact size with small footprint for easy storage and carrying
- Continuous light intensity control for comfortable viewing with specimens of various thickness and color
- › Leica EZTube™ binocular and monocular tubes with integrated eyepieces prevent loss
- Provides continuous 360° tube rotation for shared viewing and easy storage

Flexibility:

- > Pre-configured outfits for easy ordering
- Choice of monocular or binocular tube depending on budget









Leica DM100

- Affordable entry-level microscope
- > Fixed stage with stage clips for accurate manual specimen manipulation
- Pre-centered, pre-focused condenser lens built into the stage for student-friendly operation
- Clearly labeled disc diaphragm for matching aperture with objective for maximum resolution
- > Commonly configured with monocular tube for economy


Leica DM300


- > Second level microscope for full lab sessions
- Built-in mechanical stage with low position X/Y controls for accurate specimen movement at high magnifications
- Pre-centered, pre-focused professional condenser system for maximizing illumination
- Clearly labeled adjustable iris diaphragm for fine tuning the image resolution
- Commonly configured with binocular tube for comfortable viewing during longer lab sessions


Outfit Matrix

ATTENTION: POWER CORD MUST BE ORDERED SEPARATELY		13 613 301	13 613 302	13 613 303	13 613 304	13 613 305
		Leica DM100 LED, Monoc, Fixed Stage, Disc Diaphragm, E1 4×, 10×, 40×, Dust Cover, User Documents	Leica DM300 LED, Monoc, Mechanical Stage, Abbe Condenser, E1 4×, 10×, 40×, Dust Cover, User Documents	Leica DM300 LED, Monoc, Mechanical Stage, Abbe Condenser, E1 4×, 10×, 40×, 100×, oil, Dust Cover, User Documents	Leica DM300 LED, Binoc, Mechanical Stage, Abbe Condenser, E1 4×, 10×, 40×, 100×, oil, Dust Cover, User Documents	Leica DM300 LED, Binoc, Mechanical Stage, Abbe Condenser, E2 Plan 4×, 10×, 40×, 100×, oil, Dust Cover, User Documents
Stands						
13 613 310	Leica DM100 Stand, Fixed Stage, Disc Diaphragm, Dust Cover, User Documents	X				
13 613 311	Leica DM300 Stand, Mechanical Stage, Abbe Condenser, Dust Cover, User Documents		X	X	X	X
Tubes						
13 613 320	Monocular Leica EZTube™ with eyeguard and pointer	Х	X	X		
13 613 322	Binocular Leica EZTube™ with eyeguards, with pointer in right eyepiece				X	Х
E1 Objecti	ves					
13 394 000	Achromat 4×/0.10	X	X	X	X	
13 394 005	Achromat 10×/0.25	X	X	X	X	
13 394 010	Achromat 40×/0.65	X	X	X	X	
13 394 015	Achromat 100×/1.25 oil			X	X	
E2 Plan Ob	jectives					
13 494 020	Plan Achromat 4×/0.10					X
13 494 025	Plan Achromat 10×/0.25					Х
13 494 030	Plan Achromat 40×/0.65					Х
13 494 035	Plan Achromat 100×/1.25 oil					Х
Accessori	es					
13 614 800	Immersion oil, 10 ml			Х	Х	Х


Dimensions








System Diagram




Hard storage case

13 613 361



Soft storage case

10 447 477



BASIC COMPONENTS

13 613 331 13 613 332	10×/18 eyepiece without pointer 10×/18 eyepiece with pointer
13 613 333	10×/18 eyepiece with reticule scale
13 613 320 13 613 321	Monocular EZTube [™] with pointer Monocular EZTube [™] without pointer
13 613 322	Binocular EZTube™ with pointer
13 613 323	Binocular EZTube™ without pointer
13 613 324	Open binocular tube
13 613 310	Leica DM100 Stand with fixed stage and disc diaphragm
13 613 311	Leica DM300 Stand with mechanical xy-stage and Abbe condenser
13 394 000	Objective Achromat 4×/0.10 NA
13 394 005	Objective Achromat 10×/0.25 NA
13 394 010	Objective Achromat 40×/0.65 NA
13 394 015	Objective Achromat 100×/1.25 (oil)
13 494 020	Objective Planachromat 4×/0.10
13 494 025 13 494 030	Objective Planachromat 10×/0.25
13 494 030	Objective Planachromat 40×/0.65 Objective Planachromat 100×/1.25 (oil)
10 704 000	Objective Flandeni offiat 100×/ 1.25 (011)

OPTIONS


10 447 477	Soft storage case
13 613 361	Hard storage case
13 614 800	Immersion oil 10 ml
13 613 363	Simple polarization kit
13 613 360	Attachable mirror

REPLACEMENTS

13 613 300-10	00	User Document
13 596 010	Dus	t cover
13 613 362	Pair	of eyeguards
13RFAG3000	3	Replacement Fuse

INTERNATIONAL POWER CORDS

13 613 900	U.S.	
13 613 901	Europe Continental	()
13 613 902	U.K.	. :
13 613 903	Switzerland	0
13 613 904	Denmark	٥
13 613 905	Italy	(
13 613 906	Australia	
13 613 907	China	
13 613 908	Japan	
13 613 909	Israel	(3)
13 613 910	South Africa	
13 613 911	India	
13 613 912	Argentina	(4)





Specifications Leica DM100 & DM300

SEPARATE EYEPIECES

- > High eyepoint
- 10×/18 eyepieces fixed
- Available with or without pointer and with a measuring reticule
- > Foldable eyequards
- > 23.2 mm mounting diameter

EZTUBE™ MONOCULAR TUBE

- 45 degree viewing angle
- > 10×/18 eyepiece integrated into eyetube
- > Attached to stand with 2 set screws
- Rotatable mounting
- › Available with and without pointer

STAND

- Stand shape protects controls
- > Stand construction die-cast aluminium
- External fuses
- › Knurled nosepiece control
- 4 position nosepiece
- Drop in holder for 32 mm mounted or not mounted filters

EZTUBE™ BINOCULAR TUBE

- > Preset diopters for corrected vision
- > 30° viewing angle
- 10×/18 high eyepoint eyepieces integrated into eyetubes
- > Attached to stand with 2 set screws
- Rotatable mounting
- > Available with and without pointer
- Interpupillary distance range52 mm 75 mm

OPEN BINOCULAR TUBE

- Accepts separate 10×/18 eyepieces
- > Left eyetube with diopter focus
- > 30° viewing angle
- > Attached to stand with 2 set screws
- Rotatable mounting
- Interpupillary distance range52 mm 75 mm

EZLITE™ ILLUMINATION

- › Preset field aperture
- LED illumination 6000 K temp, 25,000 h life at full intensity
- Continuous intensity adjustment
- Illumination enough for viewing at lowest intensity
- > Simple polarizing kit available

CONDENSER

- > Prefocused and precentered condenser
- Leica DM100 NA = 0.65 –
 Disc diaphragm with magnification indicators
- Leica DM300 NA = 0.9/1.25 oil –
 Adjustable diaphragm with magnification labels

STAGE

- Leica DM100 Fixed Size:
 13.0 cm (X) × 12.4 cm (Y)
- › Leica DM300 Mechanical Right handed
- > Size: $13.5 \text{ cm}(X) \times 13.5 \text{ cm}(Y)$
- \rightarrow Travel: 7.8 cm (X) \times 3.6 cm (Y)
- Front loading specimen holder for one standard slide

FOCUS

- Coaxial focus controls
- > Self-adjusting focus mechanism
- 300 microns per fine focus rotation
- > Calibrated in 3 micron increments

CERTIFICATIONS

> cULus, CE, RoHS

SHIPPING

- Dimensions: 45 cm × 31.5 cm × 42 cm
- > Weight: 6.5 kg