

## EASYCARE® PRESSURE REGULATOR

The **EASYCARE®** two stage pressure regulator is suitable for direct mounting on oxygen cylinders. The structure is very compact and lightweight and it is particularly suitable for oxygen therapy. The body is made of brass and chrome-plated aluminum with an integrated impact resistant polymer calibrated orifices flowmeter with 10 options of flow oxygen supply. It is equipped with a pre-calibrated overpressure safety valve, and with a terminal unit (optional) connected to the first stage chamber which allows to get an additional and separate source of oxygen or air supplied at 4 bar. The inlet connection is offered in several options, as per the different reference standards of the destination Countries, and the outlet too is available with threads adapted to different applications. The pressure calibration of the individual stages is fixed and a pressure gauge allows to get view of the cylinder contents. A protective silicone cover prevents gauge damages caused by possible shocks received during transport or use.

The small size structure and the particular technical configuration allow the **EASYCARE®** pressure reducers to get flows of medical gases like oxygen dispensed with extreme accuracy, even in the most difficult conditions, such as in mobile units of emergency.

In fact, being the integrated flowmeter a calibrated orifices type, there is no need to get it always and only used in the upright position, as required in case of use of pressure regulator fitting conventional variable area flowmeters with vertical indicator.



01



02



03

- 01 Ergonomic knob
- 02 Easy reading of the O<sub>2</sub> flow; ten reading values to improve low flows regulation
- 03 Detail of optional outlet



#### EASYCARE®

Sizes (LxWxH)	146.5x54.5x118 mm (without optional outlet)
Weight	1.00 Kg
Maximum inlet pressure	200 bar
Gases options	O <sub>2</sub> • AIR
Standard flow range	6 L/min. • 14 L/min. • 15 L/min. • 30 L/min.
Flow rates	10 (0+9 preset values)
Flowmeter accuracy	±10% read value or ±0.5 L/min. (±0.2 L/min. for flow < than 1 L/min.) if greater
Inlet connection to the cylinder	UNI 11144 • EN 850 • NF-E 29-656 • BS 341-3 • DIN 477-1 • ISO 5145
Outlet connection	1/4" ISO 3253 M. • 3/8" ISO 3253 M. • M12x1.25 M. • 9/16" UNF EN 13544-2 M.
Terminal unit (optional)	AFNOR NF-S 90-116 • UNI 9507