



ECOtwin

Modernized user-friendliness
antepartum fetal monitor

7" wide TFT color LCD monitor (800 x 480)
Easy data transfer through USB stick
450 hours patient data saving
High sensitive 9 elements 0.985 MHz transducer
Waterproof probes
Built-in battery and printer
Networkable with PC (RS-232 or optional Bluetooth)
Including probes, event maker, belts, gel and paper



medical **ECONET**

GERMANY

Specifications

Ultrasound
Multicrystal transducer
Pulsed doppler
Ultrasound frequency : 0.985 MHz
Intensity: <10mW / cm ²
FHR range: 50 ~ 240 bpm
FHR accuracy: ± 2% of range
Dual doppler
Waterproof (IPX 7)
UC (Uterine Contraction)
External type
Frequency response: DC ~ 0,5 MHz
Reference (Zero) Control
Measurement range: 0 ~ 99
Waterproof IPX7
FM (Fetal Movement)
Detection method: Ultrasound
Dual FM
AST (Acoustic Simulator: Optional)
Vibration function waking fetus
Display
7" wide TFT color LCD
Heart rhythm
Printing state
Record speed: 1, 2, 3 cm / min
Auto Print 10, 20, 30, 40, 50, 60 min
Alarm on / off state LED
Sound
Doppler sound with volume control
HR sound
Key sound
Printer paper out
Probe fault
Low battery
Alarm sound

Printer
Thermal array roll type (width: 150 mm)
Record speed: 1, 2, 3 cm / min
Record contrast: mode 1, 2, 3
Auto record period : Off, 10, 20, 30, 40, 50, 60 min
Set-up
Alarms upper / lower value
Time & date
Print Contrast 1, 2, 3
Print speed & zoom
FHR volume level
Function
Mark function
UC reference
Zoom in particular response
Signal Interface
RS - 232 C serial interface
Bluetooth Central Interface: (Optional)
Environmental Specifications
Temperature Range
Operating: 10 to 45 °C
Storage: -10 to 50 °C
Relative Humidity Range
Operating: 30 ~ 85 %
Storage: 20 ~ 95 %
Power Specifications
Power Requirements: 100 - 240VAC, 50/60 Hz, about 80 VA
Output: DC +15V 2.5A
Battery: Rechargeable
Optional Accessories
Mobile trolley and wall mount

medical **ECONET**
GERMANY

Im Erlengrund 20, 46149 Oberhausen - Germany

t: +49 (0)208 / 377 890 - 0 info@medical-econet.com
f: +49 (0)208 / 377 890 - 55 www.medical-econet.com

CE 0123

distributor

*All specifications are subject to change without notice.