

ReproScan LED



rural mixed practice just got easier



ReproScan LED



Applications:

- Dairy Reproduction
- Equine Reproduction & Lameness
- Small Animal
- Beef Pregnancy Testing
 Compatible with ReproArm
 for extension arm preg testing





SPECIFICATIONS

| | 5 Probes Options (Transducers) | 6.5 MHz linear rectal |
|------|-----------------------------------|---|
| | | 6.5 MHz C20 micro-convex |
| | | 3.5 MHz C60 convex |
| | | 7.5 MHz linear T handle |
| | | 4.0 MHz convex rectal |
| | Probe Frequency Range | 2.0 to 10.0 MHz |
| | Battery Type | Lithium ion 11.1 VDC 58 Wh |
| | Battery Duration | Up to 4 hours per battery |
| | Battery Charge Time | 3 hours |
| | Battery Charger | Plug-in 120/240 VAC or 12VDC Car Charger |
| | Battery Level Indicator | Indicated on display |
| | Menu & Settings | Intuitive arrow driven controls |
| | Depth of Scan | 4-22 cm, depending on the probe used |
| | Measurement | Calipers— up to 4 measurements at one time |
| | Freeze | Easy access Freeze button |
| | Cine Loop | 225 frames |
| | Image Storage | Internal 100 images or store to USB |
| | Temperature Range | -10°C to 40°C (5°F to 104°F) |
| | Dimensions | 15x 21x 5 cm / 6 x 8.25 x 2 inches |
| | Weight | 1.4 kgs / 3.0 lbs (including battery) |
| | Warranty | 24 months on ultrasound and probe |
| 1000 | | 6 months on lithium ion battery |
| | Viewing Options | Bright built in 14 cm (5.5 in.) LED Screen |
| | (NTSC/PAL signal) | Goggles (multiple options are available) Adaptable to most viewing systems |
| | ReproArm Compatible | Yes with 4.0 MHz convex rectal probe |
| | | |

1-877-890-2411 www.repro-scan.com inquiry@repro-scan.com